



SMA SMART HOME Compatibility List for the Sunny Home Manager 2.0

Table of Contents

1	Content and Structure of this Document	4
2	Monitoring	5
2.1	Energy Monitoring	5
2.1.1	Energy Meter	5
2.1.1.1	SMA Energy Meter	5
2.1.2	Consumption meter	5
2.1.2.1	Energy meter from Shelly	5
2.1.3	Radio-Controlled Sockets	5
2.1.3.1	Radio-controlled sockets from Edimax	6
2.1.3.2	Radio-controlled sockets from AVM	6
2.1.3.3	Radio-controlled sockets from Niko	6
2.1.3.4	Radio-controlled sockets from Shelly	6
2.1.4	I/O Systems (digital outputs) with measuring function	7
2.1.4.1	I/O systems from Shelly with measuring function	7
2.2	Temperature Monitoring	7
2.2.1	AVM Temperature Display	7
2.3	Meter Monitoring and Status Display	7
3	External System Control	9
3.1	I/O systems from MOXA (digital inputs)	9
4	Smart Home Control Equipment	10
4.1	Radio-Controlled Sockets	10
4.1.1	Radio-controlled sockets from Edimax	10
4.1.2	Radio-controlled sockets from AVM	10
4.1.3	Radio-controlled sockets from Niko	10
4.1.4	Radio-controlled sockets from Shelly	10
4.2	I/O Systems (Digital Outputs)	11
4.2.1	I/O systems from MOXA	11
4.2.2	I/O systems from Shelly	11
5	Electrical Loads	13
5.1	Home appliances from Bosch and Siemens	13
5.1.1	Dishwashers from Bosch and Siemens	13
5.1.2	Clothes dryers from Bosch and Siemens	15
5.1.3	Washing machines from Bosch and Siemens	16
5.1.4	Washer-dryers from Bosch and Siemens	16
5.2	Heat pumps	17
5.2.1	Switching Devices for Heat Pumps with SG-Ready Interface	17
5.2.1.1	Switching devices from Moxa	17
5.2.1.2	Switching devices from Shelly	17
5.2.1.3	Switching devices from SMA	18
5.2.2	Heat pumps from AEG Haustechnik	19
5.2.3	Heat pumps from Stiebel Eltron	20
5.2.4	Heat pumps from Tecalor	21
5.2.5	Vaillant Heat Pumps	22
5.3	Heating elements	23
5.3.1	Heating rods from my-PV	23
5.4	E-mobility	23
5.4.1	Charging stations for electric vehicles	23
5.4.1.1	Charging stations from SMA	23
5.4.1.2	Charging stations from Mennekes	24

6	Energy Generators and Storage Systems	25
6.1	SMA PV Inverters.....	25
6.2	SMA Battery Inverters	25
6.3	SMA Hybrid Inverters.....	26

1 Content and Structure of this Document

This document provides an overview of the products that are compatible with the use of Sunny Home Manager 2.0 (HM-20):

- Monitoring products
- Load control products
- Products for energy generation and storage

Software version

This document is valid for Sunny Home Manager 2.0 from software version 2.14.0.R.

Monitoring products

The Sunny Home Manager supports simple monitoring of different values without using these values for direct control. This information is visualized in Sunny Portal.

Load control products

As an energy manager for systems equipped with PV systems, the Sunny Home Manager offers solutions for load control of devices from different manufacturers. Loads can include, for example, appliances for the household, heating and hot water preparation as well as e-mobility.

In principle there are the following types of load control for this:

- Indirect control, e.g. via a radio-controlled socket or a relay
Radio-controlled sockets and relays enable communication with a wide range of devices that cannot be controlled by the Sunny Home Manager via a direct data connection.
- Direct control, e.g. via the an EEBus or SEMP interface
Loads with a direct data connection to the Sunny Home Manager can be included in energy management without detailed configuration. The Sunny Home Manager automatically exchanges all load-relevant information directly with the appliances in the household and includes the load optimally in the planning process.
- Direct control via the SG-Ready interface
When connecting a load with electronic control input (e.g. SG Ready or trigger input), the control input signals will be supplied by a relay with a floating switching output. The load is hard-wired to the power supply and always has power. The control input is activated via the relay of the actuator and the load starts.

Products for energy generation and storage

The Sunny Home Manager receives the data of the energy generated by the PV system directly from the connected SMA inverters. If third-party inverters or other generators are also installed in the PV system, the Sunny Home Manager takes over the measurement data for the generated energy from an intermediate energy meter.

Battery inverters can temporarily store the energy generated by the PV system and make it available when needed. The Sunny Home Manager makes it possible to optimally schedule and use this temporarily stored energy.

Additional information

SMA offers the option to use the protocol interface SEMP at <https://developer.sma.de/on-site-integration>.

Information on the EEBus communication interface and the EEBus protocol you find under <https://www.eebus.org/>

2 Monitoring

2.1 Energy Monitoring

In energy monitoring, the entire energy flows in the household are recorded. Both the amount of energy generated by the PV system and the energy consumption of connected loads can be measured.

2.1.1 Energy Meter

Energy meters measure the power export, grid-supplied power and PV generation but do not measure the power consumption.

2.1.1.1 SMA Energy Meter

The Sunny Home Manager supports the following energy meter:

Product	Firmware version
SMA Energy Meter 10	from 1.0.4.R
SMA Energy Meter 20	from 2.0.4.R

2.1.2 Consumption meter

Consumption meters measure power consumption.

2.1.2.1 Energy meter from Shelly

The Sunny Home Manager supports the following energy meter:

Product	EAN/GTIN
Shelly 1PM	3800235262016
Shelly 1L	3800235262450
Shelly 2	–
Shelly 2.5	3800235262023
Shelly 4Pro	–
Shelly Plus 1PM	3800235265017
Shelly Plus 1PM mini	3800235265666
Shelly Pro 1PM	3800235268018
Shelly Pro 2PM	3800235268032
Shelly Pro 4PM	3800235268049
Shelly 3EM	3800235262214
Shelly Pro 3EM	3800235268100

2.1.3 Radio-Controlled Sockets

The measuring function of the radio-controlled sockets can be used to record the energy consumption of individual electrically connected loads, e.g. household appliances.

2.1.3.1 Radio-controlled sockets from Edimax

For the compatibility of the Wi-Fi radio-controlled sockets from Edimax with the Sunny Home Manager, the firmware versions of the devices must be taken into account:

Product	Firmware version
SP-2101W	up to 2.08
SP-2101W V2	from 1.00
SP-2101W V3	from 4.04

2.1.3.2 Radio-controlled sockets from AVM

The Sunny Home Manager supports AVM radio-controlled sockets in combination with a FRITZ!Box with DECT function. The FRITZ!OS version of the FRITZ!Box must be taken into account:

Product	FRITZ!Box, FRITZ!OS version
FRITZ!DECT 200	from 5.5
FRITZ!DECT 210	from 6.0

2.1.3.3 Radio-controlled sockets from Niko

The Sunny Home Manager supports Niko radio-controlled sockets in combination with a Niko Home Control hub. The version of the hub must be taken into account:

Series	Product	Niko Home Control, hub version
Radio-controlled socket, wall socket type	552-80698 / 552-80699 ¹⁾	from 2.15
Radio-controlled socket, flush socket type	170-34505 / 170-33505 ¹⁾	from 2.15
Niko Home Control starter kit energy including the Niko Home Control hub + 3 x radio-controlled socket, wall socket type	552-99098 / 552-99099 ¹⁾	from 2.15
Connected Controller for Niko Home Control II	550-00003	from 2.15

2.1.3.4 Radio-controlled sockets from Shelly

If various operating modes are possible, only relay operation is supported. Integration of an I/O system from Shelly into, e.g., window shutter operation (Shelly 2.5) is not possible. The Sunny Home Manager supports the following Shelly radio-controlled sockets:

Product	EAN/GTIN
Shelly Plug	3809511201879
Shelly Plug S	3800235262061
Shelly Plus Plug S	3800235265567

¹⁾ Socket with pin-earthing

2.1.4 I/O Systems (digital outputs) with measuring function

2.1.4.1 I/O systems from Shelly with measuring function

The measuring function can be used to record the energy consumption of individual electrically connected loads. The Sunny Home Manager uses the digital outputs of the following I/O systems with a measuring function to control devices (e.g., SG-ready devices):

Type	Product	EAN/GTIN	Communication standard
I/O system with measuring function	Shelly 1PM	3800235262016	Wi-Fi
I/O system with measuring function	Shelly 1L	3800235262450	Wi-Fi
I/O system with measuring function	Shelly 2	–	Wi-Fi
I/O system with measuring function	Shelly 2.5	3800235262023	Wi-Fi
I/O system with measuring function	Shelly 4Pro	–	Wi-Fi
I/O system with measuring function	Shelly Plus 1PM	3800235265017	Wi-Fi
I/O system with measuring function	Shelly Plus 1PM mini	3800235265666	Wi-Fi
I/O system with measuring function	Shelly Pro 1PM	3800235268018	LAN, Wi-Fi
I/O system with measuring function	Shelly Pro 2PM	3800235268032	LAN, Wi-Fi
I/O system with measuring function	Shelly Pro 4PM	3800235268049	LAN, Wi-Fi

2.2 Temperature Monitoring

2.2.1 AVM Temperature Display

The Sunny Home Manager supports the display of the device temperature in combination with a FRITZ!Box with DECT function. The FRITZ!OS version of the FRITZ!Box must be taken into account:

Product	FRITZ!Box, FRITZ!OS version
Radio-controlled socket FRITZ!DECT 200	from 5.5
Radio-controlled socket FRITZ!DECT 210	from 6.0
Radiator regulators FRITZ!DECT 301	from 7.2

2.3 Meter Monitoring and Status Display

The current status of the grid supply and the grid feed-in can be displayed via an LED lamp and thus support you in your load control.

The Sunny Home Manager supports AVM LED lamps in combination with a FRITZ!Box with DECT function. The FRITZ!OS version of the FRITZ!Box must be taken into account:

Product	FRITZ!Box, FRITZ!OS version
LED lamp FRITZ!DECT 500	from 7.2

3 External System Control

The PV system can be connected to a ripple control receiver via a compatible I/O system. This allows grid operators to control the feed-in power of the connected SMA inverters at levels of 100%, 60%, 30% and 0%.

3.1 I/O systems from MOXA (digital inputs)

The Sunny Home Manager uses the digital inputs of the following I/O systems to process ripple control signals:

Type	Product	Part number	Communication standard
I/O system	ioLogik E1214	EIO-E1214	Modbus

4 Smart Home Control Equipment

Via a compatible radio-controlled socket or a compatible relay, a variety of devices that cannot communicate directly with the Sunny Home Manager can be connected to and switched by the Sunny Home Manager.

4.1 Radio-Controlled Sockets

4.1.1 Radio-controlled sockets from Edimax

For the compatibility of the Wi-Fi radio-controlled sockets from Edimax with the Sunny Home Manager, the firmware versions of the devices must be taken into account:

Product	Firmware version
SP-2101W	up to 2.08
SP-2101W V2	from 1.00
SP-2101W V3	from 4.04

4.1.2 Radio-controlled sockets from AVM

The Sunny Home Manager supports AVM radio-controlled sockets in combination with a FRITZ!Box with DECT function. The FRITZ!OS version of the FRITZ!Box must be taken into account:

Product	FRITZ!Box, FRITZ!OS version
FRITZ!DECT 200	from 5.5
FRITZ!DECT 210	from 6.0

4.1.3 Radio-controlled sockets from Niko

The Sunny Home Manager supports Niko radio-controlled sockets in combination with a Niko Home Control hub. The version of the hub must be taken into account:

Series	Product	Niko Home Control, hub version
Radio-controlled socket, wall socket type	552-80698 / 552-80699 ²⁾	from 2.15
Radio-controlled socket, flush socket type	170-34505 / 170-33505 ²⁾	from 2.15
Niko Home Control starter kit energy including the Niko Home Control hub + 3 x radio-controlled socket, wall socket type	552-99098 / 552-99099 ²⁾	from 2.15
Connected Controller for Niko Home Control II	550-00003	from 2.15

4.1.4 Radio-controlled sockets from Shelly

If various operating modes are possible, only relay operation is supported. Integration of an I/O system from Shelly into, e.g., window shutter operation (Shelly 2.5) is not possible. The Sunny Home Manager supports the following Shelly radio-controlled sockets:

Product	EAN/GTIN
Shelly Plug	3809511201879

²⁾ Socket with pin-earthing

Product	EAN/GTIN
Shelly Plug S	3800235262061
Shelly Plus Plug S	3800235265567

4.2 I/O Systems (Digital Outputs)

4.2.1 I/O systems from MOXA

The Sunny Home Manager uses the digital outputs of the following I/O systems to control SG-ready devices (e.g., heat pumps):

Type	Product	Part number	Communication standard
I/O system	ioLogik E1214	EIO-E1214	Modbus

4.2.2 I/O systems from Shelly

The Sunny Home Manager uses the digital outputs of the following I/O systems to control devices (e.g., SG-ready devices):

Type	Product	EAN/GTIN	Communication standard
I/O system	Shelly 1	3800235262009	Wi-Fi
I/O system with measuring function	Shelly 1PM	3800235262016	Wi-Fi
I/O system with measuring function	Shelly 1L	3800235262450	Wi-Fi
I/O system with measuring function	Shelly 2	–	Wi-Fi
I/O system with measuring function	Shelly 2.5	3800235262023	Wi-Fi
I/O system	Shelly 3EM (internal relay for optional consumers)	3800235262214	Wi-Fi
I/O system with measuring function	Shelly 4Pro	–	Wi-Fi
I/O system	Shelly Pro 1	3800235268001	LAN, Wi-Fi
I/O system	Shelly Pro 2	3800235268025	LAN, Wi-Fi
I/O system	Shelly Plus 1	3800235265000	Wi-Fi
I/O system	Shelly Plus 1 Mini	3800235265659	Wi-Fi
I/O system with measuring function	Shelly Plus 1PM	3800235265017	Wi-Fi
I/O system with measuring function	Shelly Plus 1PM mini	3800235265666	Wi-Fi

Type	Product	EAN/GTIN	Communication standard
I/O system with measuring function	Shelly Pro 1PM	3800235268018	LAN, Wi-Fi
I/O system with measuring function	Shelly Pro 2PM	3800235268032	LAN, Wi-Fi
I/O system with measuring function	Shelly Pro 4PM	3800235268049	LAN, Wi-Fi

5 Electrical Loads

This list contains a selection of electrical loads which, according to the manufacturers, can communicate directly or indirectly with the Sunny Home Manager and has been compiled according to the manufacturers' specifications. Not all devices have been tested by SMA in conjunction with the Sunny Home Manager.

5.1 Home appliances from Bosch and Siemens

Below are listed home appliances of the brands Bosch and Siemens of BSH Hausgeräte GmbH, which are equipped with a communication module that supports a connection to the Sunny Home Manager.

Unfortunately, the new connectivity module launched by BSH in 2021 does not support the EEBus function, which is why this generation of devices cannot be controlled by the Sunny Home Manager and thus cannot be integrated into the energy management of the Sunny Home Manager.

5.1.1 Dishwashers from Bosch and Siemens

The following dishwashers from Bosch and Siemens are equipped with a communication module that supports connection to the Sunny Home Manager:

Series	Product	Sold	Communication standard
Bosch Series 6	SBA68PD06E	Germany	EEBus
	SBE68TX26E	Germany	EEBus
	SBI68TS06E	Germany	EEBus
	SBV68TX06E	Germany	EEBus
	SMA68PD06E	Germany	EEBus
	SME68TX26E	Germany	EEBus
	SMI68TS06E	Germany	EEBus
	SMS68NW06E	Germany	EEBus
	SMU68TS06E	Germany	EEBus
	SMS68TW06E	Germany	EEBus
	SMV68TX06E	Germany	EEBus

Series	Product	Sold	Communication standard
Bosch Series 8	SMI88TS16D	Germany	EEBus
	SMI88TS06E	Germany	EEBus
	SMI88US36E	Germany	EEBus
	SMA88TD36E	Germany	EEBus
	SMS88TI36E	Germany	EEBus
	SMS88UI36E	Germany	EEBus
	SMS88US36E	Germany	EEBus
	SMV88TX16D	Germany	EEBus
	SMV88TX06E	Germany	EEBus
	SMV88UX36E	Germany	EEBus
	SBA88TD36E	Germany	EEBus
	Siemens iQ500	SN258I06TE	Europe
SN258W06TE		Europe	EEBus
SN458B06TS		Europe	EEBus
SN558S06ME		Europe	EEBus
SN558S06TE		Europe	EEBus
SN558S16PE		Europe	EEBus
SN658X06TE		Europe	EEBus
SN658X16PE		Europe	EEBus
SN758X06TE		Europe	EEBus
SN758X46TE		Europe	EEBus
SN778D16TE		Europe	EEBus
SN858D06PE		Europe	EEBus
SX558S06TE		Europe	EEBus
SX658X06TE		Europe	EEBus
SX758X06TE		Europe	EEBus
SX758X46TE		Europe	EEBus
SX858D06PE		Europe	EEBus
SX858D36TE		Europe	EEBus

Series	Product	Sold	Communication standard
Siemens IQ700	SN278I36TE	Europe	EEBus
	SN278I36UE	Europe	EEBus
	SN478S16TD	Europe	EEBus
	SN478S36TE	Europe	EEBus
	SN478S36UE	Europe	EEBus
	SN578S16TD	Europe	EEBus
	SN578S36TE	Europe	EEBus
	SN578S36UE	Europe	EEBus
	SN678X16TD	Europe	EEBus
	SN678X36TE	Europe	EEBus
	SN678X36UE	Europe	EEBus
	SN878D26PE	Europe	EEBus
	SX678X36TE	Europe	EEBus
	SX678X36UE	Europe	EEBus
	SX878D26PE	Europe	EEBus

5.1.2 Clothes dryers from Bosch and Siemens

The following dryers from Bosch and Siemens are equipped with a communication module that supports connection to the Sunny Home Manager:

Series	Product	Sold	Communication standard
Bosch Home Professional	WTYH7701	Germany	EEBus
	WTYH7781	Germany	EEBus
	WTY887W6	Germany	EEBus
	WTX87E90	Germany	EEBus
	WTX87E40	Germany	EEBus
Bosch Series 8	WTX87M40	Germany	EEBus
	WTX87M20	Germany	EEBus
	WTX87K90	Germany	EEBus
	WTX87K80	Germany	EEBus
Siemens avantgarde	WT47X940EU	Germany, Austria	EEBus
Siemens iQ800	WT7YH701	Germany, Austria	EEBus

5.1.3 Washing machines from Bosch and Siemens

The following washing machines from Bosch and Siemens are equipped with a communication module that supports connection to the Sunny Home Manager:

Series	Product	Sold	Communication standard
Bosch Home Professional	WAV28E41	Germany	EEBus
	WAYH2842	Germany	EEBus
	WAYH2891	Germany	EEBus
	WAYH8748	Germany	EEBus
	WAYH8749	Germany	EEBus
	WAX32F90	Germany	EEBus
	WAX32E90	Germany	EEBus
Bosch Series 8	WAV28K40	Germany	EEBus
	WAV28M40	Germany	EEBus
Siemens avantgarde	WM14U840EU	Germany, Austria	EEBus
	WM14U940EU	Germany, Austria	EEBus
Siemens iQ700	WM14VL40	Germany, Austria	EEBus
	WM14VM40	Germany, Austria	EEBus
	WM14VMG1	Germany, Austria	EEBus
Siemens iQ800	WM14VG40	Germany, Austria	EEBus
	WM16XE90	Germany, Austria	EEBus
	WM16XF90	Germany, Austria	EEBus
	WM4YH748	Germany, Austria	EEBus
	WM4YH749	Germany, Austria	EEBus
	WM4YH7W0	Germany, Austria	EEBus
	WM6YH842	Germany, Austria	EEBus
	WM6YH891	Germany, Austria	EEBus

5.1.4 Washer-dryers from Bosch and Siemens

The following washing machines with dryer function from Bosch and Siemens are equipped with a communication module that supports connection to the Sunny Home Manager:

Series	Product	Sold	Communication standard
Bosch Series 6	WDU28512	Germany, Austria, Luxembourg	EEBus
	WDU28592	Germany, Austria, Luxembourg	EEBus

Series	Product	Sold	Communication standard
Siemens iQ500	WD14U512	Germany, Austria, Luxembourg	EEBus
	WD14U592	Germany, Austria, Luxembourg	EEBus

5.2 Heat pumps

Heat pumps are divided into three different types. This has an influence on the type of connection to the Sunny Home Manager.

ON/OFF heat pumps are heat pumps whose compressor runs with a constant speed during operation and draws a constant level of power. There are three control options for ON/OFF heat pumps:

- Control via radio-controlled sockets
- Direct control via the SG-Ready interface of the heat pump
- Direct control via a communication standard (SEMP or EEBus)

Inverter heat pumps are heat pumps where the rotating speed of the compressor during operation is controlled in such a way that, in accordance with the available temperature profile, an optimum performance level is achieved. The heat pump control is able to adjust the energy consumption according to the situation. There are two control options for inverter heat pumps:

- Direct control via the SG-Ready interface of the heat pump
- Direct control via a communication standard (SEMP or EEBus)

Integral systems as well as air-to-water heat pumps and brine-to-water heat pumps perform the function of ventilation in addition to space- and water heating. They can be controlled by the Sunny Home Manager if they communicate via a communication standard.

According to the manufacturer, the heat pumps listed below can be controlled directly by the Sunny Home Manager.

5.2.1 Switching Devices for Heat Pumps with SG-Ready Interface

Models that have an SG Ready interface can be found in the SG Ready database: <https://www.waermepumpe.de/normen-technik/sg-ready/sg-ready-datenbank/>

5.2.1.1 Switching devices from Moxa

Type	Product	Part number	Communication standard
I/O system	ioLogik E1214	EIO-E1214	Modbus

5.2.1.2 Switching devices from Shelly

Type	Product	EAN/GTIN	Communication standard
I/O system	Shelly 1	3800235262009	Wi-Fi
I/O system with measuring function	Shelly 1PM	3800235262016	Wi-Fi
I/O system with measuring function	Shelly 1L	3800235262450	Wi-Fi
I/O system with measuring function	Shelly 2	–	Wi-Fi

Type	Product	EAN/GTIN	Communication standard
I/O system with measuring function	Shelly 2.5	3800235262023	Wi-Fi
I/O system	Shelly 3EM (internal relay for optional consumers)	3800235262214	Wi-Fi
I/O system	Shelly Pro 3EM (internal relay for optional consumers)	3800235268100	LAN, Wi-Fi
I/O system with measuring function	Shelly 4Pro	–	Wi-Fi
I/O system	Shelly Pro 1	3800235268001	LAN, Wi-Fi
I/O system	Shelly Pro 2	3800235268025	LAN, Wi-Fi
I/O system	Shelly Plus 1	3800235265000	Wi-Fi
I/O system	Shelly Plus 1 Mini	3800235265659	Wi-Fi
I/O system with measuring function	Shelly Plus 1PM	3800235265017	Wi-Fi
I/O system with measuring function	Shelly Plus 1PM mini	3800235265666	Wi-Fi
I/O system with measuring function	Shelly Pro 1PM	3800235268018	LAN, Wi-Fi
I/O system with measuring function	Shelly Pro 2PM	3800235268032	LAN, Wi-Fi
I/O system with measuring function	Shelly Pro 4PM	3800235268049	LAN, Wi-Fi

5.2.1.3 Switching devices from SMA

Type	Product	Type designation	Communication standard
Inverter with multifunction relay	Sunny Boy 2500TL Single Tracker	SB 2500TLST-21	Speedwire
Inverter with multifunction relay	Sunny Boy 3000TL Single Tracker	SB 3000TLST-21	Speedwire
Inverter with multifunction relay	Sunny Boy 3000TL	SB 3000TL-21	Speedwire
Inverter with multifunction relay	Sunny Boy 3600TL	SB 3600TL-21	Speedwire
Inverter with multifunction relay	Sunny Boy 4000TL	SB 4000TL-21	Speedwire
Inverter with multifunction relay	Sunny Boy 5000TL	SB 5000TL-21	Speedwire
Inverter with multifunction relay	Sunny Boy Storage 3.7	SBS3.7-10	Speedwire
Inverter with multifunction relay	Sunny Boy Storage 5.0	SBS5.0-10	Speedwire

Type	Product	Type designation	Communication standard
Inverter with multifunction relay	Sunny Boy Storage 6.0	SBS6.0-10	Speedwire
Inverter with multifunction relay	Sunny Tripower 8000TL	STP 8000TL-10	Speedwire
Inverter with multifunction relay	Sunny Tripower 10000TL	STP 10000TL-10	Speedwire
Inverter with multifunction relay	Sunny Tripower 12000TL	STP 12000TL-10	Speedwire
Inverter with multifunction relay	Sunny Tripower 15000TL	STP 15000TL-10	Speedwire
Inverter with multifunction relay	Sunny Tripower 17000TL	STP 17000TL-10	Speedwire
Inverter with multifunction relay	Sunny Tripower 15000TL Economic Excellence	STP 15000TLEE-10	Speedwire
Inverter with multifunction relay	Sunny Tripower 20000TL Economic Excellence	STP 20000TLEE-10	Speedwire
Inverter with multifunction relay	Sunny Tripower Smart Energy 5.0	STP5.0-3SE-40	Speedwire
Inverter with multifunction relay	Sunny Tripower Smart Energy 6.0	STP6.0-3SE-40	Speedwire
Inverter with multifunction relay	Sunny Tripower Smart Energy 8.0	STP8.0-3SE-40	Speedwire
Inverter with multifunction relay	Sunny Tripower Smart Energy 10.0	STP10.0-3SE-40	Speedwire

5.2.2 Heat pumps from AEG Haustechnik

Type	Series	Product	Communication standard
ON/OFF heat pump	WPT	220 EL	Radio-controlled socket
		300 EL	Radio-controlled socket
		300 EL plus	Radio-controlled socket

5.2.3 Heat pumps from Stiebel Eltron

The following heat pumps are able to use the SEMP data protocol in conjunction with the Stiebel Eltron ISG web and the EMI software module or can be operated with the Sunny Home Manager in conjunction with a radio-controlled socket:

Type	Series	Product	Communication standard
ON/OFF heat pumps	Stiebel WWK	220 electronic	SMA radio-controlled socket
		300 electronic	SMA radio-controlled socket
		300 electronic SOL	SMA radio-controlled socket
		221 electronic	SMA radio-controlled socket
		301 electronic	SMA radio-controlled socket
		301 electronic SOL	SMA radio-controlled socket
Integral systems	Stiebel LWZ	303/403 (Integral/SOL) from manufacture date 08/2008	SEMP
		303/404 (SOL)	SEMP
		304/404 Trend	SEMP
		304/404 flex	SEMP
		504	SEMP
		5/8 CS Premium	SEMP
		8 CS Trend	SEMP
		5 S Plus	SEMP
		5 S Smart	SEMP
		5/8 S Trend	SEMP

Type	Series	Product	Communication standard
Air-to-water heat pumps	Stiebel WPL	10/19/24 I(K)	SEMP
		13/20 A basic	SEMP
		13-23 E (cool)	SEMP
		34/47/57	SEMP
		10/15/19/20/24/25 A(C)(S)	SEMP
		07/09/13/17 ACS classic	SEMP
		09/17 I(K)CS classic	SEMP
	Stiebel WPL-A	05/07 H(K) 230 Premium	SEMP
Brine-to-water heat pumps	Stiebel WPF	20-66 / HT	SEMP
		04-16 (cool)	SEMP
		10/13/16 M	SEMP
	Stiebel WPC	04-13 (cool)	SEMP
	Stiebel WPE-I	04-15 H(K)(W) 230 Premium	SEMP
Water-to-water heat pumps	Stiebel WPW	06-22 Set	SEMP
		10-22 trend	SEMP
	Stiebel WPW-I	07-22 H 400 Premium	

5.2.4 Heat pumps from Tecalor

The following heat pumps are able to use the SEMP data protocol in conjunction with the Tecalor ISG web and the EMI software module or can be operated with the Sunny Home Manager in conjunction with a radio-controlled socket:

Type	Series	Product	Communication standard
ON/OFF heat pumps	Tecalor TTA	220 electronic	SMA radio-controlled socket
		300 electronic	SMA radio-controlled socket
		300 electronic SOL	SMA radio-controlled socket
		221 electronic	SMA radio-controlled socket
		301 electronic	SMA radio-controlled socket
		301 electronic SOL	SMA radio-controlled socket

Type	Series	Product	Communication standard
Integral systems	Tecalor THZ	303/403 (Integral/SOL) from manufacture date 08/2008	SEMP
		304/404 (SOL)	SEMP
		304/404 Trend	SEMP
		304/404 flex	SEMP
		5.5/8.5 flex	SEMP
		5.5/8.5 flex (cool)	SEMP
		5.5/304/404 eco	SEMP
		504	SEMP
Air-to-water heat pumps	Tecalor TTL	9.5/10/13.5 I(K)	SEMP
		13/20 A basic	SEMP
		13-23 E (cool)	SEMP
		34/47/57	SEMP
		3.5/4.5/5.6/6.5/7.6/8.5/9.5/10/13.5/15/20/25 A(C)(S)	SEMP
		4.5/8.5 I(K)CS	SEMP
Brine-to-water heat pumps	Tecalor TTF	10/13/16 M	SEMP
		20-66 / HT	SEMP
		04-16 (cool)	SEMP
		4.6-15.6 (cool)	SEMP
	Tecalor TTC	04-13 (cool)	SEMP
		4.6-15.6 (cool)	SEMP
Water-to-water heat pumps	Tecalor TTW	06-22 Set	SEMP

5.2.5 Vaillant Heat Pumps

The Vaillant heat pumps have to be connected to the local network (router) via a Vaillant communication unit (VR 920 or VR 921). The Sunny Home Manager (from firmware version 2.02) supports the following Vaillant heat pumps:

Type	Series	Product	Sold	Communication standard
Air-to-water heat pumps	aroTHERM	VWL _/2	Germany, Austria, Belgium, Denmark, Finland, Luxembourg, Netherlands, Sweden, Switzerland	EEBus
		VWL _/3		EEBus
		VWL _/5		EEBus

Type	Series	Product	Sold	Communication standard
Air-to-water heat pumps	aroTHERM Split	VWL _/5	Germany, Austria, Belgium, Denmark, Finland, Luxembourg, Netherlands, Sweden, Switzerland	EEBus
	aroTHERM plus	VWL _/6		EEBus
Heat pumps	flexoCOMPACT exclusive	VWL _/4	Germany, Austria, Belgium, Denmark, Finland, Luxembourg, Netherlands, Sweden, Switzerland	EEBus
	flexoTHERM exclusive	VWL _/4		EEBus
Air-to-water heat pumps installed indoors	recoCOMPACT exclusive	VWL _/5	Germany, Austria, Belgium, Denmark, Finland, Luxembourg, Netherlands, Sweden, Switzerland	EEBus
	versoTHERM plus	VWL _/5		EEBus

5.3 Heating elements

5.3.1 Heating rods from my-PV

Not compatible if the control type **SMA Direct Meter Communication** is set on the my-PV device.

Product	Communication standard
AC ELWA-E	SEMP
AC ELWA 2	SEMP
AC •Thor	SEMP
AC •Thor 9s	SEMP

5.4 E-mobility

5.4.1 Charging stations for electric vehicles

5.4.1.1 Charging stations from SMA

The Sunny Home Manager supports a maximum of 3 SMA EV Charger per PV system.

Series	Product	Communication standard
SMA EV Charger	EVC7.4-1AC-10 (from version 1.2.x.R)	SEMP
	EVC22-3AC-10 (from version 1.2.x.R)	SEMP

5.4.1.2 Charging stations from Mennekes

Series	Product	Communication standard
Mennekes AMTRON	Xtra	SEMP
	Premium	SEMP
	Professional (from version 5.22)	SEMP
	Charge Control (from version 5.22)	SEMP

6 Energy Generators and Storage Systems

6.1 SMA PV Inverters

Device type		From inverter firmware version
Sunny Boy	SB 3000TL-21 / SB 3600TL-21 / SB 4000TL-21 / SB 5000TL-21 / SB 6000TL-21	2.00.00.R ³⁾
	SB1.5-1VL-40 / SB2.0-1VL-40 / SB2.5-1VL-40	2.03.01.R
	SB3.0-1AV-40 / SB3.6-1AV-40 / SB4.0-1AV-40 / SB5.0-1AV-40	1.02.18.R
	SB3.0-1AV-41 / SB3.6-1AV-41 / SB4.0-1AV-41 / SB5.0-1AV-41 / SB6.0-1AV-41	3.10.18.R
	SB 2500TLST-21 / SB 3000TLST-21	2.00.27.R ³⁾
Sunny Tripower	STP3.0-3AV-40 / STP4.0-3AV-40 / STP5.0-3AV-40 / STP6.0-3AV-40 / STP8.0-3AV-40 / STP10.0-3AV-40	02.11.09.R
	STP 50-40	01.01.19.R
	STP 8000TL-10 / STP 10000TL-10 / STP 12000TL-10 / STP 15000TL-10 / STP 17000TL-10	2.33.02.R ³⁾
	STP 5000TL-20/STP 6000TL-20/STP 7000TL-20/STP 8000TL-20/STP 9000TL-20/STP 10000TL-20/STP 12000TL-20	2.00.15.R
	STP 15000TLEE-10 / STP 20000TLEE-10	2.10.20.R
	STP 15000TL-30 / STP 20000TL-30 / STP 25000TL-30	02.80.04.R
	STP 12-50 / STP 15-50 / STP 20-50 / STP 25-50	2.2.7.R

For inverters without an integrated Speedwire interface, the Speedwire/Webconnect data module SWDM-10 may also be required.

6.2 SMA Battery Inverters

Device type		From inverter firmware version
Sunny Boy Storage	SBS2.5-1VL-10	02.02.01.R
	SBS3.7-10 / SBS5.0-10 / SBS6.0-10	01.00.63.R

³⁾ This firmware version is the minimum requirement for the function **Limiting of the active power feed-in**.

Device type		From inverter firmware version
Sunny Island	SI 6.0H- / SI 8.0H (without peak shaving)	01.00.xx.R
	SI3.0M-11 / SI4.4M-11 SI3.0M-11 / SI4.4M-11 / SI6.0H-11 / SI8.0-11 With SMA Speedwire data module Sunny Island SWDMSI-NR10 (without peak shaving)	1.00.00.R
	SI4.4M-12 / SI6.0H-12 / SI8.0H-12	01.00.xx.R
	SI4.4M-13 / SI6.0H-13 / SI8.0H-13	3.0x.xx.R

6.3 SMA Hybrid Inverters

Device type		From inverter firmware version
Sunny Boy	SB 3600SE-10 / SB 5000SE-10 (without time period control for charging the battery storage system, without peak shaving)	2.3.35.R
	Sunny Tripower STP5.0-3SE-40 / STP6.0-3SE-40 / STP8.0-3SE-40 /STP10.0-3SE-40	1.00.08.R

ENERGY
THAT
CHANGES



www.SMA-Solar.com

